



Paver Sand

Product Data Sheet

Version 1.1

OneMix Paver Sand is made from a fine graded sand, and is combined with our high quality bonding agent to ensure a balanced connection between pavers. OneMix is manufactured in Australia in a state of the art production facility using the latest weighing, mixing and packaging technology.

Features and Benefits

- Suitable for the professional or home handy person
- Consistent quality sand ensures high performance
- Gap Sand reduces weed growth and insect infestation by establishing a firm join between pavers
- When exposed to rain or re-wet from hosing, Paver Sand will form a flexible gel which returns to a firm bond when completely dry
- Convenient and easy to use

Applications

OneMix Paver Sand is suitable for filling joints in a wide range of block and brick paving projects. **OneMix Paver Sand** is ideal for use in driveways, areas of high wind and pool surrounds.

OneMix Paver Sand is not recommended for areas that will be subject to continuous moisture exposure.

Directions for Use

Pavers should be laid in accordance with Paver Manufacturer's instructions.

Pour **OneMix Paver Sand** as required over the pavers and use a stiff broom to thoroughly sweep the product into the gaps between the pavers. Ensure the sand between the joint is level with the Pavers.

Remove any excess Paver Sand and ensure that all gaps are filled with no product left on the actual pavers.

Using a garden hose with a nozzle on mist setting, wet down the entire surface. Avoid heavy spraying or flooding of areas. Leave to dry completely and avoid traffic on the area until completely dry.

Packaging and Yield

OneMix Paver Sand is available in **rainproof** 20kg plastic bags.

Storage and Shelf Life

OneMix Paver Sand can be stored outside (if unopened).

Provided the bag is not damaged, **OneMix Paver Sand** can be stored for an extended period without any loss of performance. Once opened it is recommended to use the entire contents of the bag.

Precautions

When handling the product wear protective gloves and clothing, including eye and face protection.

Use only outdoors or in a well ventilated area.

Seek medical advice/attention if skin, eye or respiratory irritation occurs.

For further safety information refer to the Sunstate Cement website for current Safety Data Sheets.

Limitations

- **OneMix Paver Sand** has no cementitious materials and will not stay permanently bound like mortar. **OneMix Paver Sand** is not recommended where pavers are continuously exposed to moisture.
- If Paver Sand is wet it will behave like wet sand.



A DIVISION OF SUNSTATE CEMENT LTD

8 Bulk Terminals Drive
Port of Brisbane QLD 4178

Administration 07 3895 9800
Sales 07 3895 9890

www.onemix.com.au

Sunstate Cement Ltd reserves the right to change product specifications without prior notification. Information in this publication and otherwise provided to users is given in good faith and is accurate to the best of our knowledge at the time of publication. No warranty is given or implied with respect to either the information or suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application.