



OneMix Concrete

Product Data Sheet

Version 2.0

01/08/2020

OneMix Concrete is a ready to use proportioned blend of cement, aggregate and sand suitable for applications where a quality concrete is required. OneMix is manufactured in Australia in a state of the art production facility using the latest weighing, mixing and packaging technology.

Features and Benefits

- Suitable for the professional or home handy person
- Consistent quality cement, aggregate and sand ensures high performance
- Compressive strength of 25MPa when fully cured
- Convenient and easy to use

Applications

OneMix Concrete is well suited for smaller concreting jobs such as pathways, slabs, footings and garden edging. OneMix Concrete is also suitable for securing posts and uprights in the ground etc.

Directions for Use

Using a wheel barrow or mechanical mixer, add approximately 75% of the water to the mixing vessel. Slowly add the contents of the OneMix Concrete bag. Add additional water to achieve a workable mix.

Do not over water, too much water will reduce the strength of the concrete.

Place the mixed concrete into well supported forms. Compact or tamp the concrete ensuring all corners and edges are filled.

Finish the surface with a steel trowel (smooth finish) or wooden float (coarse finish).

Cure the concrete, keeping it moist for several days by covering with plastic sheeting or damp hessian.

Concrete properties can be affected by extreme weather. Avoid mixing and placing concrete if the temperature is below 5°C or above 35°C.

Packaging and Yield

OneMix Concrete is available in rainproof 20kg and 30kg plastic bags.

One cubic metre of mixed concrete will require approximately 102 x 20kg bags or 68 x 30kg bags.

Storage and Shelf Life

OneMix Concrete can be stored outside (if unopened).

Provided the bag is not damaged, OneMix Concrete can be stored for an extended period without any loss of performance. Once opened it is recommended to use the entire contents of the bag.

Precautions

OneMix Concrete contains cement. Exposure to cement can cause skin and eye irritation and may cause respiratory irritation.

When handling the product wear protective gloves and clothing, including eye and face protection.

Use only outdoors or in a well ventilated area. Seek medical advice/attention if skin, eye or respiratory irritation occurs.

For further safety information refer to the OneMix website for current Safety Data Sheets.



Sunstate Cement maintains a certified quality management system that complies with the requirements of ISO 9001.

A DIVISION OF SUNSTATE CEMENT LTD.

Administration Tel (07) 3895 9800 Fax (07) 3895 9801
Sales Tel (07) 3895 9890 (Fax) 07 3895 9891
Email sales@sunstatecement.com.au

ABN: 58 010 421 879
8 Bulk Terminals Drive Port of Brisbane Qld 4178
PO Box 350 Wynnum Qld 4178
www.sunstatecement.com.au

For more information about OneMix and its products, please visit the OneMix website at www.onemix.com.au or email sales@sunstatecement.com.au

Sunstate Cement Ltd reserves the right to change product specifications without prior notification. Information in this publication and otherwise supplied to users is given in good faith and at the time of publication was accurate to the best of our knowledge. No warranty is given or is to be implied with respect to either the information or the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application.

Copyright © 2010 Sunstate Cement Ltd.